

Airbase Make-up Risk assessment

HAZARD	CAUSE/RISK	CONTROL MEASURE
REACTION TO PRODUCTS	IRRITATION SWELLING, REDNESS	REMOVE PRODUCT IMMEDIATELY, APPLY A COLD COMPRESS AND SEEK MEDICAL ADVICE IF NECESSARY.
EJECTION OF MATERIALS	PRODUCTS IN CLIENTS EYES	POINT THE BOTTLES DOWNWARDS AWAY FROM CLIENTS FACES.
SPILLAGE	CONTAMINATION SLIPPING HAZARD	WIPE UP ANY SPILLAGES IMMEDIATELY
MANUAL HANDLING	SPILLING OF PRODUCTS, LIFTING CASES	BEND AT THE KNEES WHEN LIFTING AIRBASE CASE.
FALLING EQUIPMENT	POSITIONED INCORRECTLY ON WORK SURFACE	ALWAYS WORK WITH THE COMPRESSOR ON A FLAT SURFACE. THE VIBRATIONS CAN CAUSE THE COMPRESSOR TO MOVE. CHECK FOR ANY TRAILING WIRES.
ELECTRICAL EQUIPMENT	PAT TESTED FAULTY/EXPOSED WIRES	THE COMPRESSOR IS PAT TESTED ANNUALLY ONCE IT IS A YEAR OLD. CHECK FOR ANY FRAYING WIRES AND CONNECTIONS.
PRODUCTS	IRRITATIONS, SPECIFIC USAGE	CHECK FOR CONTRA-INDICATIONS AND ALLERGIES AS PER CONTRA INDICATIONS SHEET.
ENVIRONMENTAL RISKS	VENTILATION	WHEN SPRAYING AIRBASE WORK IN A WELL VENTILATED ROOM. IF THERE ARE NO WINDOWS MAKE SURE THERE IS AN EXTRACTOR FAN. DO NOT EAT OR DRINK IN AN AREA WHERE YOU MAY BE SPRAYING.
INFECTIONS	CROSS CONTAMINATION	USE A SPATULA WHEN DECANTING THE PRIMER. WIPE THE NECK OF THE FOUNDATION BOTTLES.
BREATHING DIFFICULTIES	RESPIRATORY	ADVISE ANY CLIENT WITH RESPIRATORY DISEASES THAT THE SPRAYING MAY AFFECT THEIR BREATHING. BE SURE TO GET CONSENT BEFORE PROCEEDING WITH THE APPLICATION AND IF BREATHING BECOMES DIFFICULT CEASE THE TREATMENT.
OTHER HAZARDS	NEVER SPRAY INTO THE EARS, EYES, NOSE AND MOUTH DO NOT EXCEED 10PSI ON THE FACE AND 3-4PSI AROUND THE EYES NEVER REMOVE THE CAP FROM THE GUN TO EXPOSE THE INTERNAL NEEDLE	